



## Rechargeable Sealed Lead-Acid Battery

# PS-605

## 6 Volt 0.5 Amp. Hrs.



### Features:


- Absorbent Glass Mat (AGM) technology for superior performance.
- Valve regulated, spill proof construction allows safe operation in any position.
- Power/volume ratio yielding unrivaled energy density.
- Rugged ABS plastic case and cover
- Approved for transport by air. D.O.T., I.A.T.A., F.A.A. and C.A.B. certified.
- U.L. recognized under file number MH 20845.




### PERFORMANCE SPECIFICATIONS

<b>Nominal Voltage</b> .....	6 volts (3 cells in series)
<b>Nominal Capacity</b>	
20 hour rate (25mA to 5.25 volts) .....	0.50 A.H.
10 hour rate (45mA to 5.25 volts) .....	0.45 A.H.
5 hour rate (80mA to 5.10 volts) .....	0.40 A.H.
1 hour rate (300mA to 4.50 volts) .....	0.30 A.H.
<b>Approximate Weight</b> .....	0.20 pounds (0.09 kg)
<b>Energy Density (20 hour rate)</b> .....	1.24 Watt-hours/cubic inch (75.2 Watt-hours/l)
<b>Specific Energy (20 hour rate)</b> .....	15 Watt-hours/pound (33.3 Watt-hours/kg)
<b>Internal Resistance (Fully Charged Battery)</b> .....	360 milliohms (approximately)
<b>Maximum Discharge Current Using Standard Terminals</b> .....	1.0 amperes
<b>Terminals</b> .....	"WL": wire leads with Molex connector 5264-02 housing & 5263-PBT plug
<b>Shelf Life — % of nominal capacity at 68° F (20° C)</b>	
1 Month.....	97%
3 Months.....	91%
6 Months.....	83%
<b>Operating Temperature Range</b>	
<b>Charge</b> .....	-4°F (-20°C) to 122°F (50°C)
<b>Discharge</b> .....	-4°F (-20°C) to 140°F (60°C)
<b>Case</b> .....	ABS Plastic


**Shelf Life and Storage**




**Discharge Characteristics**




**Life Characteristics in Stand-By Use**




**Discharge Time vs. Discharge Current**



**Life Characteristics in Cyclic Use**



Physical Dimensions: in. (mm)



Tolerances are +/- 0.04 in. (+/- 1mm) and +/- 0.08 in. (+/- 2mm) for height dimensions. All data subject to change without notice.

**CHARGING**

**Cycle Applications:** Limit initial current to 100 mA. Charge until battery voltage (under charge) reaches 7.20 to 7.35 volts at 68°F (20°C). Hold at 7.20 to 7.35 volts until current drops to approximately 5 mA. Battery is fully charged under these conditions, and charger should either be disconnected or switched to "float" voltage.

**"Float" or "Stand-By" Service:** Hold battery across constant voltage source of 6.75 to 6.90 volts continuously. When held at this voltage, the battery will seek its own current level and maintain itself in a fully charged condition.

**NOTE:** Due to the self-discharge characteristics of this type of battery, it is imperative that they be charged after 6-9 months of storage, otherwise permanent loss of capacity might occur as a result of sulfation.



DISTRIBUTED BY:  
 COAST ENERGY CORPORATION, INC.  
 1924 First St. San Fernando, CA 91340  
 Tel: 818-361-6461 Fax: 818-898-3219  
 customerservice@wilpowerbattery.com



ISO9001-2000  
 FM39170

www.wilpowerbattery.com